

Specifications



Eaton FWP-400A

Eaton Bussmann series FWP high speed fuse, 1400 Vac (FWS 8-15A), 2100 Vac (FWS 2-6A), 1000 Vdc (FWL/FWS 2-30A), 400A RMS, 200 kAIC Vac, 50 kAIC at 700 Vdc, Non Indicating, High speed fuse, Blade end X blade end, Stud

General specifications

PRODUCT NAME	Eaton Bussmann series FWP high speed fuse
CATALOG NUMBER	FWP-400A
UPC	051712150439
PRODUCT LENGTH/DEPTH	2.4 in
PRODUCT HEIGHT	5.4 in
PRODUCT WIDTH	2.9 in
PRODUCT WEIGHT	1.7 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Recognized CSA Certified

Electrical rating

AMPERAGE RATING	400A RMS
INTERRUPT RATING	200 kAIC Vac 50 kAIC at 700 Vdc
VOLTAGE RATING	1400 Vac (FWS 8-15 A), 2100 Vac (FWS 2-6 A), 1000 Vdc (FWL/FWS 2-30 A)
WATT LOSSES	78 W

General information

CONNECTION	Blade end x blade end
FUSE INDICATOR	Non Indicating
MOUNTING METHOD	Stud

Physical details

PACKAGING TYPE	Standard
-----------------------	----------

Resources

CATALOGS	Bussmann series complete full line catalog no. 1007
CERTIFICATION REPORTS	Eaton Bussmann EU Declaration of conformity 93-68-EEC2007
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - FWP-400A
TECHNICAL DATA SHEETS	eaton-bussmann-series-fwp-50-1200-amps-north-american-fuses-datasheet-720012-en-gb.pdf Bussmann series FWP series 5-1200A fuse data sheet no. 720012
TECHNICAL SERVICE BULLETINS	Datasheet - FNQ-30

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

